

LOUVER DORMER ROUND TOP

DIMENSIONS AVAILABLE:

W	H	LOUVER DEPTH:
12"	18"	3"
18"	36"	3"
24"	36"	3"
24"	48"	3"
30"	60"	3"
36"	60"	3"

12" FLANGE SOLDERED OR SEALED WATERTIGHT

4" FLANGE IN FRONT

3" DEEP LOUVER W/ BUG SCREEN, SET BACK 1/2" FROM FACE

LOUVER FREE AREA:

12"	18"	35 SQ. IN.
18"	36"	138 SQ. IN.
24"	36"	176 SQ. IN.
24"	48"	254 SQ. IN.
30"	60"	384 SQ. IN.
36"	60"	461 SQ. IN.

AVAILABLE MATERIALS:

COPPER	ZINC/ TIN COATED COPPER	PREWEATHERED ZINC	PATINA COPPER
PREFINISHED ALUMINUM/ STEEL	PAINT GRIP STEEL		

REV. 7/14

INSTALLATION:

MARK OPENING IN ROOF DECK ON DESIRED COURSE. CUT OPENING IN DECK. POSITION DORMER OVER OPENING AND FASTEN TO DECK.

OTHER INFORMATION:

SPECIFY EXACT ROOF PITCH.

OTHER:

INCLUDES INSECT SCREEN OF COMPATIBLE MATERIAL.

COPPER CRAFT
A EURAMAX COMPANY

6-08